LED PANEL LIGHTS

TECHNICAL SPECIFICATIONS

CCT	4000K (3000/5000K on request)
CRI	>80Ra
INPUT VOLTAGE	AC100-240V (AC220-277V for the EP6060 model)
PF	≥0.90
POWER FREQUENCY	50/60Hz
LIFETIME	>50,000 hrs.
WORKING TEMPERATURE	-45°C to +55°C
IP GRADE	IP54
LED DRIVER	External
LED LIGHT SOURCE	EPISTAR
THERMAL MANAGEMENT	Passive
SURFACE FINISH	Aluminum
MOUNTING	Surfaced, recessed or suspended



RoHS WEEE COMPLIANT CE IP54

Code	Power	CCT	Luminous Flux	Dimensions (mm)	Driver	Warranty
VER-EP6060-32-840	32W	4000K	3,200 lm	595x595x9	Lifud	3 years
VER-DIMP6060-32-840					Mean Well dimmable 1-10V	5 years
VER-DALIP6060-32-840					Mean Well DALI	5 years
VER-DIMP6262-32-840	32W	4000K	3,200 lm	619x619x9	Mean Well dimmable 1-10V	5 years
VER-DIMP30120-42-840	42W	4000K	4,200 lm	1195x295x9	Mean Well dimmable 1-10V	5 years
VER-DIMP60120-70-840	70W	4000K	7,090 lm	1195x595x9	Mean Well dimmable 1-10V	5 years

VERDE LED HQ
VERDE House,
Wellington Road
Cork,
Ireland

T. + 353 - 21 - 486 - 1577
F. + 353 - 21 - 486 - 1572
E. info@verdeled.com